



NOTES

- Usable storage capacity is based on 45° angle of repose.
- Normal discharge capacity is 6.5 units per hour, however greater fuel delivery capacities are available.
- One unit is equal to 200 cubic feet or 5.664 cubic meters.



Storage Capacity in Units				"C" Dimension	
Bin	Model	Usable	Level Full	Feet	Meters
A-13	40	29	32	59'	18
	30	23	26	49'	14.9
	20	16	19	39'	11.9
	10	10	13	29'	8.8
A-17	40	48	53	63'3"	19.3
	30	38	43	53'3"	16.2
	20	27	33	43'3"	13.2
	10	16	22	33'3"	10.1
A-19	40	60	67	65'1"	19.8
	30	47	54	55'1"	16.8
	20	33	41	45'1"	13.7
	10	19	28	35'1"	10.7
A-21	40	72	82	66'9"	20.3
	30	57	67	56'9"	17.3
	20	40	51	46'9"	14.2
	10	23	35	36'9"	11.2
A-24	40	100	116	70'1"	21.4
	30	78	96	60'1"	18.3
	20	56	74	50'1"	15.3
	10	32	51	40'1"	12.2
A-30	40	152	182	75'2"	22.9
	30	118	150	65'2"	19.9
	20	83	117	55'2"	16.8
	10	46	83	45'2"	13.8

Model	"A" Dimension		"B" Dimension	
	Feet	Meters	Feet	Meters
A-13	13'4"	4.1	16'7"	5.1
A-17	17'2"	5.2	20'5"	6.2
A-19	19'1"	5.8	22'4"	6.8
A-21	21'0"	6.4	24'3"	7.4
A-24	24'10"	7.6	28'1"	8.6
A-30	30'7"	9.3	33'10"	10.3